

48V-NAV-CMD-120/240

Monitoring box allowing the control and the wiring of 1 or 2 NAVILITE 48VDC beacon, working at night only or continuously, plugged to work simultaneously or in redundancy (a main light and a backup light working only in case the main light is not working) with remote signalization in case of failure of the light or failure of the 230VAC supply. This monitoring box can also powered up to 4 NAVILITE 48VDC working simultaneously

P/N : 113912



Key Points

- Polycarbonate envelope with 4 cable entries
- Photocell integrated : 'day&night' or 'night only' operation
- Surge protection included
- alarm activated in case of failure of the 230VAC power supply or failure of the lights
- 'main & back-up operation for 2-4 lights' or working simultaneously for 1 to 4 lights
- possibility to configure 1 to 4 NAVILITE 48VDC in fixed mode or flashing mode (low intensity type E, L-810(F))

Electrical Characteristics	
Voltage	230VAC -10%/+15%
Power supply	24W
Mechanical Characteristics	
Dimensions	160 x 58 mm
IP degree	IP65 in vertical position
Weight	300g
Cable entry diameter	from 6.5 to 12 mm
Wire cross section	from 1 to 2,5 mm ²
Attachment	4 screws type M4
Position of the 4 mounting holes	148 x 50 mm